

# OUTDOOR/INDOOR EXTENSION CORDS

Part Number	Cord Size	Length	Cord Color	Rating	Standard Carton Qty.   Lbs.
-------------	-----------	--------	------------	--------	-----------------------------

## SJTW — 300 VOLT

All weather, extra flexible, -40°C. Applications include construction, industrial, and maintenance. NEMA 5-15.

C2316025OR	16/3	25'	ORANGE	13A 125V 1625W	24	47
C2316050OR	16/3	50'	ORANGE	13A 125V 1625W	12	46
C2316100OR	16/3	100'	ORANGE	10A 125V 1250W	6	43
C4314025BOLTE*	14/3	25'	ORG/BLK STRIPE	15A 125V 1875W	14	31
C4314050BOLTE*	14/3	50'	ORG/BLK STRIPE	15A 125V 1875W	10	50
C4314100BOLTE*	14/3	100'	ORG/BLK STRIPE	13A 125V 1625W	5	41
C4312025YWLTE*	12/3	25'	YELLOW	15A 125V 1875W	10	40
C4312050YWLTE*	12/3	50'	YELLOW	15A 125V 1875W	6	44
C4312100YWLTE*	12/3	100'	YELLOW	15A 125V 1875W	3	42
C4310050YB	10/3	50'	YEL/BLK STRIPE	15A 125V 1875W	1	12
C4310100YB	10/3	100'	YEL/BLK STRIPE	15A 125V 1875W	1	24



\*Quick Check® power indicator lighted end.

## SJTW, 3 OUTLET POWER BLOCK - 300 VOLT

Extra flexible, all weather, -40°C. Provides additional outlets from one source. NEMA 5-15.


C4514025BO	14/3	25'	ORG/BLK STRIPE	15A 125V 1875W	14	39
C4514050BO	14/3	50'	ORG/BLK STRIPE	15A 125V 1875W	10	50
C4514100BO	14/3	100'	ORG/BLK STRIPE	13A 125V 1625W	5	46
C4512025YW	12/3	25'	YELLOW	15A 125V 1875W	10	39
C4512050YW	12/3	50'	YELLOW	15A 125V 1875W	6	46
C4512100YW	12/3	100'	YELLOW	15A 125V 1875W	3	43
C4510050YB	10/3	50'	YEL/BLK STRIPE	15A 125V 1875W	1	13
C4510100YB	10/3	100'	YEL/BLK STRIPE	15A 125V 1875W	1	25



## SJTW, 300 VOLT LOCKING CONNECTION

Extra heavy capacity, all weather industrial outdoor/indoor. NEMA L5-20.

A9318050YW	12/3	50'	YELLOW	20A 125V 2500W	6	44
A9318100YW	12/3	100'	YELLOW	15A 125V 1875W	3	44



## SJTW, 4-OUTLET JUNCTION BOX - 300 VOLT

Rugged ABS housing. Converts single outlet to four grounded outlets. NEMA 5-15.

C1489050OR*	12/3	50'	ORANGE	15A 125V 1875W	5	39
C1489100OR*	12/3	100'	ORANGE	15A 125V 1875W	3	45

\*Not UL listed, but made to acceptable industry standards.

