



Zinc Die Cast Conduit Fittings

Non-Metallic, Armored Cable and Flexible Metallic Conduit Fittings


ARMORED CABLE & FLEXIBLE METALLIC CONDUIT CONNECTORS — UL File No. E-19189

| Squeeze Type 90° Angle Non-Insulated | Cat. # | Size | A | B | C | D | Unit Qty. | Standard Pkg. | Wt. Lbs./ 100 |
|---|--------|--------|------|------|------|------|-----------|---------------|---------------|
|  | 724DC | 3/8" | .61 | 1.31 | 1.02 | 1.77 | 25 | 250 | 8 |
| | 736DC | 1/2" | .63 | 1.62 | 1.41 | 2.09 | 15 | 150 | 11 |
| | 738DC | 3/4" | .81 | 1.88 | 1.43 | 2.30 | 12 | 120 | 15 |
| | 739DC | 1" | 1.04 | 2.28 | 1.82 | 2.83 | 5 | 50 | 25 |
| | 740DC | 1 1/4" | 1.43 | 2.73 | 2.18 | 3.89 | 4 | 40 | 41 |
| | 741DC | 1 1/2" | 1.64 | 3.61 | 3.81 | 6.01 | 2 | 12 | 117 |
| | 742DC | 2" | 2.11 | 3.62 | 3.81 | 6.10 | 2 | 12 | 119 |
| | 744DC | 2 1/2" | 2.41 | .98 | 3.91 | NA | 1 | 10 | 286 |
| | 745DC | 3" | 2.99 | 1.00 | 4.37 | NA | 1 | 4 | 405 |
| | 746DC | 3 1/2" | 3.48 | 1.00 | 5.17 | NA | 1 | 4 | 560 |
| | 747DC | 4" | 3.92 | .98 | 5.70 | NA | 1 | 3 | 642 |


ARMORED CABLE & FLEXIBLE METALLIC CONDUIT CONNECTORS — UL File No. E-19189

| Squeeze Type 90° Angle Insulated | Cat. # | Size | A | B | C | D | Unit Qty. | Standard Pkg. | Wt. Lbs./ 100 |
|--|--------|--------|------|------|------|------|-----------|---------------|---------------|
|  | 1724DC | 3/8" | .61 | 1.31 | 1.02 | 1.77 | 25 | 250 | 8 |
| | 1736DC | 1/2" | .63 | 1.62 | 1.41 | 2.09 | 15 | 150 | 11 |
| | 1738DC | 3/4" | .81 | 1.88 | 1.43 | 2.30 | 12 | 120 | 15 |
| | 1739DC | 1" | 1.04 | 2.28 | 1.82 | 2.83 | 5 | 50 | 25 |
| | 1740DC | 1 1/4" | 1.43 | 2.73 | 2.18 | 3.89 | 4 | 40 | 41 |
| | 1741DC | 1 1/2" | 1.64 | 3.61 | 3.81 | 6.01 | 2 | 12 | 117 |
| | 1742DC | 2" | 2.11 | 3.62 | 3.81 | 6.10 | 2 | 12 | 119 |
| | 1744DC | 2 1/2" | 2.41 | .98 | 3.91 | NA | 1 | 10 | 286 |
| | 1745DC | 3" | 2.99 | 1.00 | 4.37 | NA | 1 | 4 | 405 |
| | 1746DC | 3 1/2" | 3.48 | 1.00 | 5.17 | NA | 1 | 4 | 560 |
| | 1747DC | 4" | 3.92 | .98 | 5.70 | NA | 1 | 3 | 642 |

FLEXIBLE METALLIC CONDUIT FITTINGS — UL File No. E-19189

| Screw-In Type Straight Connectors Non-Insulated | Cat. # | Size | A | B | C | D | Unit Qty. | Standard Pkg. | Wt. Lbs./ 100 |
|---|--------|--------|------|------|------|------|-----------|---------------|---------------|
|  | 770DC | 3/8" | 1.28 | .37 | 1.28 | .92 | 80 | 800 | 5 |
| | 771DC | 1/2" | 1.38 | .63 | 1.38 | .93 | 60 | 600 | 5 |
| | 772DC | 3/4" | 1.56 | .81 | 1.56 | 1.18 | 35 | 350 | 9 |
| | 773DC | 1" | 1.87 | 1.00 | 1.87 | 1.36 | 15 | 150 | 13 |
| | 774DC | 1 1/4" | 2.11 | 1.26 | 2.11 | 1.73 | 10 | 100 | 24 |
| | 775DC | 1 1/2" | 2.30 | 1.50 | 2.30 | 2.11 | 6 | 60 | 34 |
| | 776DC | 2" | 2.46 | 2.00 | 2.46 | 2.66 | 3 | 30 | 49 |

FLEXIBLE METALLIC CONDUIT FITTINGS — UL File No. E-19189

| Screw-In Type Couplings | Cat. # | Size | A | B | C | D | Unit Qty. | Standard Pkg. | Wt. Lbs./ 100 |
|---|--------|--------|------|------|------|---|-----------|---------------|---------------|
|  | 791DC | 1/2" | 1.81 | .63 | .91 | — | 40 | 400 | 4 |
| | 792DC | 3/4" | 2.10 | .81 | 1.09 | — | 25 | 250 | 7 |
| | 793DC | 1" | 2.42 | 1.00 | 1.36 | — | 15 | 150 | 12 |
| | 794DC | 1 1/4" | 2.74 | 1.26 | 1.63 | — | 10 | 100 | 21 |
| | 795DC | 1 1/2" | 3.04 | 1.50 | 1.93 | — | 6 | 60 | 31 |
| | 796DC | 2" | 3.25 | 2.00 | 2.44 | — | 3 | 30 | 44 |