

































































# Rigid/Intermediate Grade Conduit Fittings




















- Insulated Throat Grounding Bushings
- Threaded and Threadless
- Copper or Aluminum Ground Lug
- 105°C Rated

Rigid Intermediate

INSULATED THROAT GROUNDING BUSHINGS						
IRON-105°C Rated						
Copper Lug – For Copper Grounding Conductors – Threaded						
UL File No. E-6225						
	Cat. #	Trade Size	Lug Size	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
	GLL-1C	1/2"	#4 – #14	50	500	8
	GLL-2C	3/4"	#4 – #14	50	250	12
	GLL-3C	1"	#4 – #14	50	250	14
	GLL-4C	1 1/4"	#4 – #14	25	125	19
	GLL-4-10C	1 1/4"	#1/0 – #8	25	125	30
	GLL-5C	1 1/2"	#4 – #14	10	100	21
	GLL-5-10C	1 1/2"	#1/0 – #8	10	100	32
	GLL-6C	2"	#4 – #14	10	50	29
	GLL-6-10C	2"	#1/0 – #8	10	50	40
	GLL-7C	2 1/2"	#1/0 – #8	10	50	65
	GLL-7-30C	2 1/2"	#3/0 – #6	10	50	88
	GLL-7-250C	2 1/2"	250MCM – #6	10	50	97
	GLL-8C	3"	#1/0 – #8	5	25	77
	GLL-8-30C	3"	#3/0 – #6	5	25	100
	GLL-8-250C	3"	250MCM – #6	5	25	109
	GLL-9C	3 1/2"	#3/0 – #6	1	1	125
	GLL-9-250C	3 1/2"	250MCM – #6	1	1	134
	GLL-10C	4"	#3/0 – #6	1	1	145
	GLL-10-250C	4"	250MCM – #6	1	1	154
	GLL-11C	5"	#3/0 – #6	1	1	165
	GLL-11-250C	5"	250MCM – #6	1	1	174
	GLL-12C	6"	#3/0 – #6	1	1	195
	GLL-12-250C	6"	250MCM – #6	1	1	204

Aluminum Lug – For Copper Or Aluminum Grounding Conductors – Threaded						
UL File No. E-6225						
	Cat. #	Trade Size	Lug Size	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
	GLL-1	1/2"	#4 – #14	50	500	5
	GLL-2	3/4"	#4 – #14	50	250	9
	GLL-3	1"	#4 – #14	50	250	12
	GLL-4	1 1/4"	#4 – #14	25	125	19
	GLL-4-10	1 1/4"	#1/0 – #8	25	125	23
	GLL-5	1 1/2"	#4 – #14	10	100	24
	GLL-5-10	1 1/2"	#1/0 – #8	10	100	28
	GLL-6	2"	#4 – #14	10	50	26
	GLL-6-10	2"	#1/0 – #8	10	50	32
	GLL-7	2 1/2"	#1/0 – #8	10	50	53
	GLL-7-30	2 1/2"	#3/0 – #6	10	50	60
	GLL-7-250	2 1/2"	250MCM – #6	10	50	67
	GLL-8	3"	#1/0 – #8	5	25	70
	GLL-8-30	3"	#3/0 – #6	5	25	72
	GLL-8-250	3"	250MCM – #6	5	25	76
	GLL-9	3 1/2"	#3/0 – #6	1	1	100
	GLL-9-250	3 1/2"	250MCM – #6	1	1	100
	GLL-10	4"	#3/0 – #6	1	1	110
	GLL-10-250	4"	250MCM – #6	1	1	120
	GLL-11	5"	#3/0 – #6	1	1	140
	GLL-11-250	5"	250MCM – #6	1	1	143
	GLL-12	6"	#3/0 – #6	1	1	160
	GLL-12-250	6"	250MCM – #6	1	1	163

Copper Lug – For Copper Grounding Conductors – Threadless – Set Screw Type						
UL File No. E-6225						
	Cat. #	Trade Size	Lug Size	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
	GLS-1C	1/2"	#4 – #14	50	500	8
	GLS-2C	3/4"	#4 – #14	50	250	12
	GLS-3C	1"	#4 – #14	50	250	14
	GLS-4C	1 1/4"	#4 – #14	25	125	19
	GLS-4-10C	1 1/4"	#1/0 – #8	25	125	30
	GLS-5C	1 1/2"	#4 – #14	10	100	21
	GLS-5-10C	1 1/2"	#1/0 – #8	10	100	32
	GLS-6C	2"	#4 – #14	10	50	29
	GLS-6-10C	2"	#1/0 – #8	10	50	40
	GLS-7C	2 1/2"	#1/0 – #8	10	50	65
	GLS-7-30C	2 1/2"	#3/0 – #6	10	50	88
	GLS-7-250C	2 1/2"	250MCM – #6	10	50	97
	GLS-8C	3"	#1/0 – #8	5	25	77
	GLS-8-30C	3"	#3/0 – #6	5	25	100
	GLS-8-250C	3"	250MCM – #6	5	25	109
	GLS-9C	3 1/2"	#3/0 – #6	1	1	125
	GLS-9-250C	3 1/2"	250MCM – #6	1	1	134
	GLS-10C	4"	#3/0 – #6	1	1	145
	GLS-10-250C	4"	250MCM – #6	1	1	154
	GLS-11C	5"	#3/0 – #6	1	1	165
	GLS-11-250C	5"	250MCM – #6	1	1	174
	GLS-12C	6"	#3/0 – #6	1	1	195
	GLS-12-250C	6"	250MCM – #6	1	1	204

Aluminum Lug – For Copper Or Aluminum Grounding Conductors – Threadless – Set Screw Type						
UL File No. E-6225						
	Cat. #	Trade Size	Lug Size	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
	GLS-1	1/2"	#4 – #14	50	500	5
	GLS-2	3/4"	#4 – #14	50	250	9
	GLS-3	1"	#4 – #14	50	250	12
	GLS-4	1 1/4"	#4 – #14	25	125	19
	GLS-4-10	1 1/4"	#1/0 – #8	25	125	23
	GLS-5	1 1/2"	#4 – #14	10	100	24
	GLS-5-10	1 1/2"	#1/0 – #8	10	100	28
	GLS-6	2"	#4 – #14	10	50	26
	GLS-6-10	2"	#1/0 – #8	10	50	32
	GLS-7	2 1/2"	#1/0 – #8	10	50	53
	GLS-7-30	2 1/2"	#3/0 – #6	10	50	60
	GLS-7-250	2 1/2"	250MCM – #6	10	50	67
	GLS-8	3"	#1/0 – #8	5	25	70
	GLS-8-30	3"	#3/0 – #6	5	25	72
	GLS-8-250	3"	250MCM – #6	5	25	76
	GLS-9	3 1/2"	#3/0 – #6	1	1	100
	GLS-9-250	3 1/2"	250MCM – #6	1	1	100
	GLS-10	4"	#3/0 – #6	1	1	110
	GLS-10-250	4"	250MCM – #6	1	1	120
	GLS-11	5"	#3/0 – #6	1	1	140
	GLS-11-250	5"	250MCM – #6	1	1	143
	GLS-12	6"	#3/0 – #6	1	1	160
	GLS-12-250	6"	250MCM – #6	1	1	163