



Zinc Die Cast Conduit Fittings

Non-Metallic, Armored Cable and Flexible Metallic Conduit Fittings


ARMORED CABLE & FLEXIBLE METALLIC CONDUIT CONNECTORS — UL File No. E-19189

Squeeze Type 90° Angle Non-Insulated	Cat. #	Size	A	B	C	D	Unit Qty.	Standard Pkg.	Wt. Lbs./100
	724DC	3/8"	.61	1.31	1.02	1.77	25	250	8
	736DC	1/2"	.63	1.62	1.41	2.09	15	150	11
	738DC	3/4"	.81	1.88	1.43	2.30	12	120	15
	739DC	1"	1.04	2.28	1.82	2.83	5	50	25
	740DC	1 1/4"	1.43	2.73	2.18	3.89	4	40	41
	741DC	1 1/2"	1.64	3.61	3.81	6.01	2	12	117
	742DC	2"	2.11	3.62	3.81	6.10	2	12	119
	744DC	2 1/2"	2.41	.98	3.91	NA	1	10	286
	745DC	3"	2.99	1.00	4.37	NA	1	4	405
	746DC	3 1/2"	3.48	1.00	5.17	NA	1	4	560
	747DC	4"	3.92	.98	5.70	NA	1	3	642


ARMORED CABLE & FLEXIBLE METALLIC CONDUIT CONNECTORS — UL File No. E-19189

Squeeze Type 90° Angle Insulated	Cat. #	Size	A	B	C	D	Unit Qty.	Standard Pkg.	Wt. Lbs./100
	1724DC	3/8"	.61	1.31	1.02	1.77	25	250	8
	1736DC	1/2"	.63	1.62	1.41	2.09	15	150	11
	1738DC	3/4"	.81	1.88	1.43	2.30	12	120	15
	1739DC	1"	1.04	2.28	1.82	2.83	5	50	25
	1740DC	1 1/4"	1.43	2.73	2.18	3.89	4	40	41
	1741DC	1 1/2"	1.64	3.61	3.81	6.01	2	12	117
	1742DC	2"	2.11	3.62	3.81	6.10	2	12	119
	1744DC	2 1/2"	2.41	.98	3.91	NA	1	10	286
	1745DC	3"	2.99	1.00	4.37	NA	1	4	405
	1746DC	3 1/2"	3.48	1.00	5.17	NA	1	4	560
	1747DC	4"	3.92	.98	5.70	NA	1	3	642

FLEXIBLE METALLIC CONDUIT FITTINGS — UL File No. E-19189

Screw-In Type Straight Connectors Non-Insulated	Cat. #	Size	A	B	C	D	Unit Qty.	Standard Pkg.	Wt. Lbs./100
	770DC	3/8"	1.28	.37	1.28	.92	80	800	5
	771DC	1/2"	1.38	.63	1.38	.93	60	600	5
	772DC	3/4"	1.56	.81	1.56	1.18	35	350	9
	773DC	1"	1.87	1.00	1.87	1.36	15	150	13
	774DC	1 1/4"	2.11	1.26	2.11	1.73	10	100	24
	775DC	1 1/2"	2.30	1.50	2.30	2.11	6	60	34
	776DC	2"	2.46	2.00	2.46	2.66	3	30	49

FLEXIBLE METALLIC CONDUIT FITTINGS — UL File No. E-19189

Screw-In Type Couplings	Cat. #	Size	A	B	C	D	Unit Qty.	Standard Pkg.	Wt. Lbs./100
	791DC	1/2"	1.81	.63	.91	—	40	400	4
	792DC	3/4"	2.10	.81	1.09	—	25	250	7
	793DC	1"	2.42	1.00	1.36	—	15	150	12
	794DC	1 1/4"	2.74	1.26	1.63	—	10	100	21
	795DC	1 1/2"	3.04	1.50	1.93	—	6	60	31
	796DC	2"	3.25	2.00	2.44	—	3	30	44