## 411/16" SQUARES COVERS - CUBIC INCH CAPACITY (SEE BELOW)







TP574, - TP582,

TP529, TP531







**TP568** 

TP569, TP570, TP571, TP573, TP575

TP584, TP586, TP589, TP593, TP541, TP543

TP851\*

TP852\*

F	n	r.	Α	ir	Р	le	n	п	m	

* For Air Plenum				
Product Number	Description	Std. Unit Pkg.	Wt. Lbs. Per 100	Capacity Cu. In.
TP568†	Flat Blank	25	40	_
TP569	½" Raised, With Ears 2¾"	25	36	3.3
TP570	Raised 5/8", With Ears 23/4"	25	38	3.8
TP571	3/4" Raised, With Ears 23/4"	25	40	5.0
TP572†	Flat, With 1/2" KO	25	40	_
TP573	1" Raised, With Ears 23/4"	25	44	7.0
TP575	11/4" Raised, With Ears 23/4"	25	48	9.0
Air Plenum				
TP851*	Flat Blank Gasketed Captive Screws	50	42	_
TP852	Flat Ring Double Gasketed	25	20	_
ONE DEVICE	-			
TP574	1/4" Raised	25	32	1.8
TP576	½" Raised	25	36	3.3
TP578	3/4" Raised	25	42	5.0
TP579	5/8" Raised	25	39	4.3
TP580	1" Raised	25	46	6.8
TP582	11/4" Raised	25	52	8.8
TP529	11/2" Raised	25	64	11.3
TP531	2" Raised	25	76	15.0
TWO DEVICE				
TP590	Flat	25	21	_
TP583	1/4" Raised	25	26	3.0
TP584	½" Raised	25	30	6.0
TP587	5⁄8" Raised	25	32	8.0
TP586	¾" Raised	25	34	8.8
TP589	1" Raised	25	38	11.7
TP593	11/4" Raised	25	42	14.0
TP541	11/2" Raised	25	63	18.8
TP543	2" Raised	25	79	24.5
† CSA Certified				

## 411/16" SQUARE SURFACE COVERS - 9.0 CUBIC INCH CAPACITY 1/2" DEEP



















TP720

TP722

**TP730 TP736** 

TP728

TP732

TP734

TP738

Product Number	Description	Std. Unit Pkg.	Wt. Lbs. Per 100
TP720	For One Toggle Switch	10	52
TP722	For One Duplex Receptacle	10	49
TP724	For One Single Receptacle 113/32" Dia.	10	53
TP730	For One 20 Amp Single Receptacle 1.620" Dia.	10	50
TP736	For One 1.730" Dia. Power Outlet	10	51
TP726	For Two Toggle Switches	10	52
TP728	For Two Duplex Receptacles	10	44
TP732	For One 2.125" Dia. Range/Dryer Receptacle	10	48
TP734	For One 2.480" Dia. Power Outlet	10	45
TP738	For One Ground Fault Interrupter	10	45
TP741	For Two GFI Receptacles	10	43