

# Porcelain Ceiling Receptacle Lampholders

Medium Base  
660W 125V  
660W 250V



## Porcelain Ceiling Receptacle Lampholders

### FEATURES

- High-strength insulator porcelain.
- Mounts on 4" (101.6mm) outlet boxes with breakout for 3.25" (82.55mm) box mounting.
- Pull chain socket interiors are removable.
- Pull chain devices include ball chain, 3' (0.91m) of cord, connector and end bell.
- Top wire versions have terminal screws backed out – ready for wiring – without removing the interior.
- Sockets available in two piece version to permit interior replacement, dust ring protects against plaster and dirt.
- Shade grooves provided on two piece version.

### Medium Base Lampholders

Rating		Description	Terminals	Switch	Color	Catalog No.
W	V					
660	250	One Piece with feed through	4 Screws Top Wire	Keyless	White	604
660	250	Two Piece with feed through	4 Screws Top Wire	Pull Chain	White	659
660	125	Two Piece w/ 15A 125V/AC 2P2W Outlet	2 Screws Top Wire	Pull Chain	White	669
660	125	Two Piece w/ 15A 125V/AC 2P3W Outlet	2 Screws Top Wire	Pull Chain	White	667




604



659



669



667

## R-2 Lampholders

### TESTING & CODE COMPLIANCE

- UL Listed, (file no. E7430) UL 496 requirements,
- Meet CSA requirements, C22.2 no. 43
- NOM Certified

### MATERIAL CHARACTERISTICS

Temperature Rating:  
-40°C to 65°C