

Kwik Stepper Step Bits



- 35884 • Unique split tip design penetrates through steel faster.
- Resists walking or skidding, even on round surfaces.
- Balanced double flute construction requires less pressure, does the work for you.
- Designed and manufactured in U.S.A.

SPECIFICATIONS

Hole Sizes: From 1/8" through 1-3/8" (3.2 - 34.9 mm)

Capacity: Cut up through 3/8" (9.5 mm) mild steel, copper, brass, aluminum, wood, plastic and laminates.

Cat. No.	UPC No.	Description
35884	35884	Kwik Stepper® Step Bit Kit
03607	03607	Kwik Stepper® Step Bit Kit

Cat. No.	UPC No.	Description	03607	35884
34401	34401	1/2" Multi-Hole Step Bit	•	•
34403	34403	7/8" Multi-Hole Step Bit	•	•
36413	36413	1-1/8" Multi-Hole Step Bit	•	•
35936	35936	Plastic Case	•	•

Single-hole bits are designed to drill one indicated hole size through a series of steps from bit tip to full size.	Multi-hole bits allow you to drill a hole in any of the stated diameters.	METRIC										
		1/2" (12.7 mm) Single-Hole Step Bit	1/2" (12.7 mm) Multi-Hole Step Bit	1/2" (12.7 mm) Multi-Hole Step Bit	11/16" (17.5mm) Multi-Hole Step Bit	13/16" (20.6 mm) Multi-Hole Step Bit	7/8" (22.2 mm) Single-Hole Step Bit	7/8" (22.2 mm) Multi-Hole Step Bit	1-1/8" (28.6 mm) Multi-Hole Step Bit	1-3/8" (34.9 mm) Multi-Hole Step Bit	9.7 mm (.382") Single-Hole Step Bit	30.5 mm (1.201") Multi-Hole Step Bit

Size		Cat./UPC No.											
Inches	mm	34410	34401	36402	30004	30005	34411	34403	36413	36414	36018	36020	36022
1/8	3.2		✓										
5/32	4.0		✓										
3/16	4.8		✓	✓	✓	✓		✓					
7/32	5.6		✓										
1/4	6.4		✓	✓	✓	✓		✓					
9/32	7.1		✓										
5/16	7.9		✓	✓	✓	✓		✓					
11/32	8.7		✓										
3/8	9.5		✓	✓	✓	✓		✓					
0.382	9.7									✓			
13/32	10.3		✓										
7/16	11.1		✓	✓	✓	✓		✓					
15/32	11.9		✓										
0.492	12.5											✓ Pg-7	
1/2	12.7	✓	✓	✓	✓	✓		✓					
9/16	14.3				✓	✓		✓					
0.598	15.2											✓ Pg-9	
5/8	15.9				✓	✓		✓					
0.638	16.2												✓ ISO-16
11/16	17.5				✓	✓		✓					
0.732	18.6											✓ Pg-11	
3/4	19.1					✓		✓					
0.803	20.4											✓ Pg-13	✓ ISO-20
13/16	20.6					✓		✓					
7/8	22.2						✓	✓	✓	✓			
0.886	22.5											✓ Pg-16	
1.00	25.4												✓ ISO-25
1.114	28.3											✓ Pg-21	
1-1/8	28.6								✓	✓			
1.201	30.5												
1-7/32	31.0												
1-1/4	31.8												
1.280	32.5												✓ ISO-32
1-3/8	34.9									✓			
Overall Length		1-5/8" (41.4 mm)	3-1/8" (79.4 mm)	3-3/16" (81.0 mm)	2-13/16" (71.4 mm)	3-3/16" (81.0mm)	2-3/16" (55.6 mm)	3-5/16" (84.1 mm)	2-1/4" (57.2 mm)	2-7/8" (73.0 mm)	1.590" (40.4 mm)	3-1/2" (88.9 mm)	3.100" (78.7 mm)
Minimum Chuck Size		1/4" (6.4 mm)	1/4" (6.4 mm)	1/4" (6.4mm)	1/4" (6.4 mm)	1/4" (6.4 mm)	3/8" (9.5 mm)	3/8" (9.5mm)	3/8" (9.5 mm)	3/8" (9.5 mm)	1/4" (6.4 mm)	3/8" (9.5 mm)	3/8" (9.5 mm)
Maximum Material Thickness		10 gauge (3.5 mm)	10 gauge (3.5 mm)	3/8" (9.5 mm)	10 gauge (3.5 mm)	10 gauge (3.5 mm)	10 gauge (3.5 mm)	10 gauge (3.5 mm)	10 gauge (3.5 mm)	10 gauge (3.5 mm)	10 gauge (3.5 mm)	1/4" (6.4 mm)	1/4" (6.4 mm)
Bit Extension		901	901	901	901	901	-	-	-	-	901	-	-