



Style T-1D Jobbers length, 135 deg. self-centering split point for drilling low tensile strength alloy materials, stainless, and other medium duty applications

Style T-1C Jobbers length, 135 deg. cobalt for drilling in tough high tensile strength material, P.H. Stainless, Titanium, and Inconel.

List Price for Each Drill Bit

Bar Code	Cat. #	Pkg.	Size	Price per ea.	Bar Code	Cat. #	Pkg.	Size	Price per ea.
94100	T-1D	12	3/64	2.69	94640	T-1C*	12	1/6	6.34
94102	T-1D	12	1/16	2.46	94641	T-1C*	12	5/64	6.34
94104	T-1D	12	5/64	2.46	94642	T-1C*	12	3/32	6.34
94106	T-1D	12	3/32	2.69	94643	T-1C*	12	7/64	6.78
94108	T-1D	12	7/64	2.69	94644	T-1C*	12	1/8	8.07
94110	T-1D	12	1/8	3.07	94645	T-1C*	12	9/64	8.69
94112	T-1D	12	9/64	3.07	94646	T-1C*	12	5/32	9.17
94114	T-1D	12	5/32	3.42	94647	T-1C*	12	11/64	9.65
94116	T-1D	12	11/64	3.56	94648	T-1C*	12	3/16	11.00
94118	T-1D	12	3/16	4.03	94649	T-1C*	12	13/64	14.22
94120	T-1D	12	13/64	4.37	94650	T-1C*	12	7/32	15.79
94122	T-1D	12	7/32	4.99	94651	T-1C*	12	15/64	16.46
94124	T-1D	12	15/64	5.38	94652	T-1C*	12	1/4	18.25
94126	T-1D	12	1/4	6.01	94653	T-1C*	12	17/64	19.60
94128	T-1D	12	17/64	7.11	94654	T-1C*	12	9/32	21.07
94130	T-1D	12	9/32	8.31	94655	T-1C*	12	19/64	24.74
94132	T-1D	12	19/64	8.88	94656	T-1C*	6	5/16	26.52
94134	T-1D	6	5/16	9.17	94657	T-1C*	6	21/64	28.83
94136	T-1D	6	21/64	9.05	94658	T-1C*	6	11/32	33.78
94138	T-1D	6	11/32	11.38	94659	T-1C*	6	23/64	38.41
94140	T-1D	6	23/64	12.77	94660	T-1C*	6	3/8	40.29
94142	T-1D	6	3/8	13.16	94661	T-1C*	6	25/64	42.04
94144	T-1D	6	25/64	14.74	94662	T-1C*	6	13/32	44.69
94146	T-1D	6	13/32	15.08	94663	T-1C*	6	27/64	47.55
94148	T-1D	6	27/64	16.71	94664	T-1C*	6	7/16	49.36
94150	T-1D	6	7/16	18.01	94665	T-1C*	6	29/64	59.48
94152	T-1D	6	29/64	20.84	94666	T-1C*	6	15/32	60.35
94154	T-1D	6	15/32	21.03	94667	T-1C*	6	31/64	62.13
94156	T-1D	6	31/64	21.94	94668	T-1C*	6	1/2	63.93
94158	T-1D	6	1/2	22.47					

*Will Break This Category Only for +15% Charge

Other size diameters and lengths available upon request.