



by Schneider Electric

List Price \$1,733.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.****Technical Characteristics**

Approvals	UL Listed - CSA Certified - IEC Rated
Circuit Breaker Type	Standard Interrupting
For Use With	Industrial Enclosures
Marketing Trade Name	Square D
AC Magnetic Trip Setting	1000A - 2000A Adjustable Trip
Ampere Rating	200A
Frame Type	K-Frame
HACR Rated	Yes
Voltage Rating	600VAC
Mounting Type	Unit Mount
Weight	7 Pounds
Number of Poles	3-Pole
Short Circuit Current Rating	25kA@480VAC
Space Required	3
Type	KA
Wire Size	(1)#4 to 350 AWG/kcmil(Al/Cu)
Width	4.50 Inches
Depth	4.75 Inches
Height	8.00 Inches

Shipping and Ordering

Category	00918 - Circuit Breakers, Thermal Magnetic, 600 Vac, Type KAL & KHL, UL, Unit Mount
Discount Schedule	DE2
Article Number	785901425663
Package Quantity	1
Weight	7.35 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Thermal-magnetic Molded Case Circuit Breakers

250, 400 Ampere Frame
Class 655, 825, 660

SQUARE D
www.SquareD.com
For the most up-to-date information



KAL/KHL
2- and 3-pole
70-250 Amperes



KIL36250



Q4-L
2- and 3-pole
250-400 Amperes

K-frame—250 A, Thermal-magnetic (600 Vac)

Ampere Rating	AC Magnetic Trip Settings▲		Standard Interrupting		High Interrupting		Current Limiting		Terminal Wire Range
	Low	High	Catalog Number	Price	Catalog Number	Price	Catalog Number	Price	
2-pole, 600 Vac, 250 Vdc									
70	350	700	KAL26070	\$1381.	KHL26070	\$3226.	AL250KA (1) #4 AWG-350 kcmil
80	400	800	KAL26080	1381.	KHL26080	3226.	
90	450	900	KAL26090	1381.	KHL26090	3226.	
100	500	1000	KAL26100	1381.	KHL26100	3226.	
110	550	1100	KAL26110	1381.	KHL26110	3226.	KIL26110	\$4118.	
125	625	1250	KAL26125	1381.	KHL26125	3226.	KIL26125	4118.	
150	750	1500	KAL26150	1381.	KHL26150	3226.	KIL26150	4118.	
175	875	1750	KAL26175	1381.	KHL26175	3226.	KIL26175	4118.	
200	1000	2000	KAL26200	1381.	KHL26200	3226.	
225	1125	2250	KAL26225	1381.	KHL26225	3226.	
250	1250	2500	KAL26250	2400.	KHL26250	4241.	
200	1000	2000	KIL26200	4118.	AL250KI (1) #1/0 AWG-350 kcmil
225	1125	2250	KIL26225	4118.	
250	1250	2500	KIL26250	4815.	
3-pole, 600 Vac, 250 Vdc									
70	350	700	KAL36070	\$1733.	KHL36070	\$3899.	AL250KA (1) #4 AWG-350 kcmil
80	400	800	KAL36080	1733.	KHL36080	3899.	
90	450	900	KAL36090	1733.	KHL36090	3899.	
100	500	1000	KAL36100	1733.	KHL36100	3899.	
110	550	1100	KAL36110	1733.	KHL36110	3899.	KIL36110	\$5169.	
125	625	1250	KAL36125	1733.	KHL36125	3899.	KIL36125	5169.	
150	750	1500	KAL36150	1733.	KHL36150	3899.	KIL36150	5169.	
175	875	1750	KAL36175	1733.	KHL36175	3899.	KIL36175	5169.	
200	1000	2000	KAL36200	1733.	KHL36200	3899.	
225	1125	2250	KAL36225	1733.	KHL36225	3899.	
250	1250	2500	KAL36250	2889.	KHL36250	5065.	
200	1000	2000	KIL36200	5169.	AL250KI (1) #1/0 AWG-350 kcmil
225	1125	2250	KIL36225	5169.	
250	1250	2500	KIL36250	6054.	

K-frame—250 A, Thermal-magnetic (480 Vac)

Ampere Rating	AC Magnetic Trip Settings▲		Extra High Interrupting		Terminal Wire Range
	Low	High	Catalog Number	Price	
2-pole, 480 Vac					
110	550	1100	KCL24110	\$3638.	AL250KA (1) #4 AWG-350 kcmil
125	625	1250	KCL24125	3638.	
150	750	1500	KCL24150	3638.	
175	875	1750	KCL24175	3638.	
200	1000	2000	KCL24200	3638.	AL250KI (1) #1/0 AWG-350 kcmil
225	1125	2250	KCL24225	3638.	
250	1250	2500	KCL24250	4460.	
3-pole, 480 Vac					
110	550	1100	KCL34110	4548.	AL250KA (1) #4 AWG-350 kcmil
125	625	1250	KCL34125	4548.	
150	750	1500	KCL34150	4548.	
175	875	1750	KCL34175	4548.	
200	1000	2000	KCL34200	4548.	AL250KI (1) #1/0 AWG-350 kcmil
225	1125	2250	KCL34225	4548.	
250	1250	2500	KCL34250	5580.	

Q4-frame—400 A, Thermal-magnetic (240 Vac)

Ampere Rating	AC Magnetic Trip Settings▲		Standard Interrupting		Terminal Wire Range
	Low	High	Catalog Number	Price	
2-pole, 240 Vac					
250	1250	2500	Q4L2250	\$2114.	AL400LA (1) #1 AWG-600 kcmil or (2) #1 AWG-250 kcmil
300	1500	3000	Q4L2300	2114.	
350	1750	3500	Q4L2350	2114.	
400	2000	4000	Q4L2400	2114.	
3-pole, 240 Vac					
250	1250	2500	Q4L3250	\$2554.	AL400LA (1) #1 AWG-600 kcmil or (2) #1 AWG-250 kcmil
300	1500	3000	Q4L3300	2554.	
350	1750	3500	Q4L3350	2554.	
400	2000	4000	Q4L3400	2554.	

Interrupting Ratings (kA)

	KAL	KHL	KCL	KIL	Q4
240 V	42	65	100	200	25
480 V	25	35	65	200	...
600 V	22	25	...	100	...

▲ UL magnetic trip setting tolerances are ±25% (low) and ±20% (high) from nominal values shown.

Accessories pages 6-36-6-38
Optional Lugs pages 6-43, 6-44
Dimensions pages 6-49, 6-50
Enclosures pages 6-51-6-54