

Product 25126 Number:

Order F60T12/CW/HO Abbreviation:

**General** 75W, 60"MOL, T12 HO (800 mA) rapid start fluorescent lamp, **Description:** Cool White phosphor, 4200K color temperature, 60 CRI

| Product Information          |                         |  |
|------------------------------|-------------------------|--|
| Abbrev. With Packaging Info. | F60T12CWHO 30/CS 1/SKU  |  |
| Actual Length (in)           | 57.720                  |  |
| Actual Length (mm)           | 1466.09                 |  |
| Average Rated Life (hr)      | 12000                   |  |
| Base                         | Recessed Double Contact |  |
| Bulb                         | T12                     |  |
| Color Rendering Index (CRI)  | 60                      |  |
| Color Temperature/CCT (K)    | 4200                    |  |
| Diameter (in)                | 1.590                   |  |
| Diameter (mm)                | 40.46                   |  |
| Industry Standards           | ANSI C78.81 - 2001      |  |
| Initial Lumens at 25C        | 5200                    |  |
| Mean Lumens at 25C           | 4212                    |  |
| Mean Lumens at 35C           | 4212                    |  |
| Nominal Length (in)          | 60.000                  |  |
| Nominal Length (mm)          | 1524.00                 |  |
| Nominal Wattage (W)          | 75.00                   |  |

## Footnotes

• Approximate initial lumens after 100 hours operation.

• The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.

• Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.

• Average life rating at 12 hours operation per start is 18,000 hours.