


EMT CONNECTORS COMPRESSION TYPE

• CONCRETE TIGHT



CAT#	A	B	C
651S/Si	1.750	1.250	.406
652S/Si	1.813	1.563	.406
653S/Si	2.000	1.813	.406
654S/Si	2.750	2.188	.500
655S/Si	3.000	2.438	.500
656S/Si	3.188	2.938	.688
657S/Si	3.875	3.688	.750
658S/Si	4.375	4.313	.938
659S/Si	4.500	4.875	.938
660S/Si	4.750	5.375	.938

TOPAZ CAT #	UPC#	SIZE	UNIT CTN	SHIP CASE	STEEL WT/ CASE
651S	16790	1/2"	25	250	30
652S	16800	3/4"	25	250	43
653S	16810	1"	10	100	25
654S	16820	1 1/4"	—	25	12
655S	16830	1 1/2"	—	20	12
656S	16840	2"	—	15	15
657S*	16844	2 1/2"	—	12	19
658S*	16842	3"	—	6	15
659S*	16843	3 1/2"	—	6	16
660S*	16844	4"	—	6	21

*EMT & RIGID

INSULATED THROAT

TOPAZ CAT #	UPC#	SIZE	UNIT CTN	SHIP CASE	STEEL WT/ CASE
651Si	16850	1/2"	25	250	30
652Si	16860	3/4"	25	250	43
653Si	16870	1"	10	100	25
654Si	16880	1 1/4"	—	25	12
655Si	16890	1 1/2"	—	20	12
656Si	16900	2"	—	15	15
657Si*	16901	2 1/2"	—	12	19
658Si*	16902	3"	—	6	15
659Si*	16903	3 1/2"	—	6	16
660Si*	16904	4"	—	6	21

*EMT & RIGID




E148716



E148716

EMT COUPLINGS COMPRESSION TYPE

• CONCRETE TIGHT



CAT#	A	B
661S	1.688	1.250
662S	2.000	1.563
663S	2.125	1.813
664S	3.063	2.188
665S	3.125	2.438
666S	3.375	2.938
667S	4.875	3.688
668S	5.250	4.313
669S	5.500	4.875
670S	5.750	5.375

TOPAZ CAT #	UPC#	SIZE	UNIT CTN	SHIP CASE	STEEL WT/ CASE
661S	17010	1/2"	25	250	32
662S	17020	3/4"	25	250	40
663S	17030	1"	10	100	31
664S	17040	1 1/4"	—	25	15
665S	17050	1 1/2"	—	20	15
666S	17060	2"	—	15	18
667S*	17061	2 1/2"	—	6	14
668S*	17062	3"	—	6	19
669S*	17063	3 1/2"	—	6	21
670S*	17064	4"	—	3	15

*EMT & RIGID



E148716