






## 861 Wood Floor Box Ordering Information

Catalog No./Item	Description/Specifications	Catalog No./Item		Description/Specifications
<b>861</b>  	<b>Wood Floor Box</b> – Die-cast aluminum construction with three 1/2" trade size knockouts; two on the sides and one on the bottom. 18 cu. in. [295 cu. cm] capacity. Requires a 4" [102mm] diameter hole. Comes complete with a disposable cover. Receptacle and activation sold separately.	<b>861QTCGY</b> <b>861QTGBK</b> <b>861QTCAL</b> <b>861QTCBS</b> <b>861QTCAB</b> <b>861QTCVY</b>  	<b>Wood Floor Box Assembly</b> – Complete with prewired 15A quad receptacle can be wired as standard or isolated ground. Flush poke-thru style cover which is available in painted gray (GY), black (BK), ivory (VY), or brushed metal finishes in aluminum (AL) and brass (BS). Slide covers match painted flange colors: gray, black, ivory. Aluminum and brass flanges shipped with black slide cover. Brass flange also available with nonmetallic brass color slide holder (AB). Die-cast aluminum construction with three 1/2" trade size knockouts; two on the sides and one on the bottom, 18 cu. in. [295 cu.cm] capacity. Requires a 4" [102mm] diameter hole and overall floor depth of 1" [25mm].	
<b>861DB</b>  	<b>Wood Floor Box Assembly</b> – Complete with 20A duplex receptacle and brass cover plate. Die-cast aluminum construction with three 1/2" trade size knockouts; two on the sides and one on the bottom. 18 cu. in. [295 cu. cm] capacity. Requires a 4" [102mm] diameter hole and overall floor depth of 1" [25mm].	<b>NOTE:</b> Assembled with scrub water gasket. For use on tile, wood, or carpet floors.		
<b>861AMDTCGY</b> <b>861AMDTGBK</b> <b>861AMDTCAL</b> <b>861AMDTCBS</b> <b>861AMDTTAB</b> <b>861AMDTTCVY</b>  	<b>Wood Floor Box Assembly</b> – All communication floor boxes accept up to four UTP connectors. Flush poke-thru-style flanges available in painted gray (GY), black (BK), ivory (VY), or brushed metal finishes in aluminum (AL) and brass (BS). Slide covers match painted flange colors: gray, black, ivory. Aluminum and brass flanges shipped with black slide cover. Brass flange also available with nonmetallic brass-color (AB) slide holder. Die-cast aluminum construction with three 1/2" trade size knock outs; two on the sides and one on the bottom. 18 cu. in. [295 cu.cm.] capacity. Requires a 4" [102mm] diameter hole and overall floor depth of 1" [25mm].	<b>861AMDRTTTCGY</b> <b>861AMDRTTGBK</b> <b>861AMDRTTTCAL</b> <b>861AMDRTTTCBS</b> <b>861AMDRTTTCAB</b> <b>861AMDRTTTCVY</b>  	<b>Wood Floor Box Assembly</b> –All communication floor boxes accept up to four UTP connectors. Flush poke-thru style flanges available in painted gray (GY), black (BK), ivory (VY), or brushed metal finishes in aluminum (AL) and brass (BS). Slide covers match painted flange colors: gray, black, ivory. Aluminum and brass flanges shipped with black slide cover. Brass flange also available with nonmetallic brass color slide holder (AB). Die-cast aluminum construction with three 1/2" trade size knockouts; two on the sides and one on the bottom, 18 cu. in. [295 cu. cm.] capacity. Requires a 4" [102mm] diameter hole and overall floor depth of 1" [25mm].	<div style="border: 1px solid black; padding: 2px; text-align: center; width: 30px; margin-bottom: 2px;"><b>ORT</b></div> <div style="border: 1px solid black; padding: 2px; text-align: center; width: 30px; margin-bottom: 2px;"><b>P&amp;S</b></div> <div style="border: 1px solid black; padding: 2px; text-align: center; width: 30px;"><b>OPEN</b></div>
<b>NOTE:</b> Assembled with scrub water gasket. For use on tile, wood, or carpet floors.	<ul style="list-style-type: none"> <li>• Includes two Pass &amp; Seymour Catalog 5e dual modular inserts and two Wiremold Open System inserts</li> </ul>	<ul style="list-style-type: none"> <li>• Includes bezel to accept four Ortronics TracJack inserts, and bezel to accept two dual Ortronics Series II modular inserts. TracJack and Series II devices sold separately.</li> </ul>		
		<b>NOTE:</b> Assembled with scrub water gasket. For use on tile, wood, or carpet floors.		