



SPECIFICATION SHEET

T8 Ballast Bypass LED Lamp

Operates with Direct Line Voltage - No Ballast Needed

Item Number **33676**

Specifications

Energy Used (Watts).....	18
Domestic Code	LED 18T8/48"/50 Ballast Bypass
Input Voltage	120/277
Brightness (Lumens)	2200
Average Rated Hours	50,000
Life (in years)*.....	45.6
Light Appearance (Kelvin).....	5000
CRI	82
Efficacy (LPW).....	122
Number of LED Modules.....	80
Minimum Starting Temperature.....	-20°C/-4°F
Estimated Yearly Energy Cost**	\$2.17
Package Type.....	Sleeve



Physical Characteristics

Finish.....	Frost
Color Designation	Daylight
Base.....	G13 (Medium BiPin)
MOL	48"



Warning

- Turn power off before inspection, installation, or removal.
- Risk of electric shock - Do not use where exposed to water or weather.
- For use in totally enclosed fixtures.
- Do not open – no user serviceable parts inside.
- This device is not intended for use with emergency exit luminaires or emergency exit lights.
- This device complies with Part 15 of the FCC rules and has been tested and found to comply with the limits for a Class B digital device. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.

* Based on 3 hrs./day

** Based on 3 hrs./day 11¢/kWh - Cost depends on rates and use.

Specifications are subject to change without notice, please visit www.westinghouselighting.com for latest information.

Call 1-800-999-2226 or visit www.westinghouselighting.com.

©, WESTINGHOUSE, and INNOVATION YOU CAN BE SURE OF are trademarks of Westinghouse Electric Corporation.

Used under license by Westinghouse Lighting. All Rights Reserved.